



Panther II Silicone Probe (1.25)

LATEST TECHNOLOGY

PERFORMANCE-DRIVEN INNOVATION

No Compromise Features

- Peizoresistive technology
- Sour service
- Robust mechanical design
- Programmable
- Quick stabilization (ideal for gradients)

Unparalleled Warranty & Service

- World-wide service
- International warranty excepting gross mechanical damage
- International maintenance agreement available
- Manufactured and serviced in Canada



P 403.309.6366 Toll Free 1.888.765.3282
7975 – 49th Avenue | Red Deer, Alberta | Canada | T4P 2V5
sales@rockdataservices.com | support@rockdataservices.com
www.rockdataservices.com

At Panther Probe, we strive to provide specifications that are reflective of actual downhole performance - not just theoretical values. If you have any unique applications or questions relating to our tools, or our "Rock Solid Guarantee", please contact us for more information.

PRESSURE

Accuracy (% of full scale)	0.03 (typical 0.025)
Resolution (% of full scale)	0.00006 or 0.02 kPa 35000 kPa gauge
Available Sensors	1.0 mPa - 103 mPa (150 psi - 15000 psi)

TEMPERATURE

Accuracy	0.5 ° C
Resolution	0.01 ° C
Operating Temperature	USB Board 150 ° C

CAPACITY

Number of Data Sets	4,000,000 sets
Battery Capacity - USB Board	375 days @ 5 sec - 1200 days @ 60 sec

PHYSICAL

Outside Diameter	1.25 inch (3.18 cm)
Length	18 inch (45.7 cm)
Tranducer Type	Silicon Crystal
Material	Hastelloy C-276 & Incolloy 718 / 925

POWER REQUIREMENTS

Voltage	3V
Source	Lithium Battery
Battery Type	1 sub CC Pack

COMMUNICATION

Type	USB
------	-----